

Metal One-touch Fittings

Applicable Tubing: Metric Size, Connection Thread: M, R, Rc

KQB2 Series

RoHS



Applicable Tubing

Tubing material	FEP, PFA, Nylon, Soft nylon, Polyurethane, Polyolefin
Tubing O.D.	ø3.2, ø4, ø6, ø8, ø10, ø12, ø16

Specifications

Fluid	Air, N ₂ , Water ^{Note 2)}
Operating pressure range ^{Note 1)}	–100 kPa to 1 MPa ^{Note 3)}
Proof pressure	3.0 MPa
Ambient and fluid temperature ^{Note 4)}	–5 to 150°C (No freezing) ^{Note 3)}
Lubricant	Grease-free specification
Seal on the threads	With sealant

Note 1) Avoid using in a vacuum holding application such as a leak tester, since there is leakage.

Note 2) Deionized water is not recommended for use as it may affect the material used in the fittings.

In addition, it is known to degrade the water quality.

Note 3) Check the operating pressure range and operating temperature range of the tubing.

Note 4) It is recommended that you use the inner sleeve in the following conditions (Except ø3.2):

- When using in an environment where the fluid temperature changes drastically.
- When using at a high temperature.

* Temperature Condition of Mounting the Inner Sleeve

Tubing	Temperature
FEP tubing/TH Series	80°C or more
Super PFA tubing/TL Series	120°C or more

Spare Parts


Description	Tubing O.D.	Part no.	Material
Gasket	—	M-5G3	Stainless steel 316, Special FKM
Bulkhead nut	ø3.2 ø4	KQB223-P01	C3604 (Electroless nickel plated)
	ø6	KQB206-P01	
	ø8	KQB208-P01	
	ø10	KQB210-P01	
	ø12	KQB212-P01	
	ø16	KQB216-P01	

Cross Reference Table of the Inner Sleeve

Tubing O.D.	Tubing material			Applicable inner sleeve	
	TUS (Soft polyurethane)	TH/TIH (FEP)	TL/TIL (Super PFA)	Part no.	Length
ø4	—	TH0402	—	TJ-0402	18
	TUS0425	TH0425	—	TJ-0425	18
	—	—	TL0403	TJ-0403	18
ø6	TUS0604	TH0604	TL0604	TJ-0604	19
	TUS0805	—	—	TJ-0805	20.5
ø8	—	TH0806	TL0806	TJ-0806	20.5
	TUS1065	—	—	TJ-1065	23
ø10	—	TH1075	—	TJ-1075	23
	—	TH1008	TL1008	TJ-1008	24
	TUS1208	—	—	TJ-1208	24
ø12	—	TH1209	—	TJ-1209	24
	—	TH1210	TL1210	TJ-1210	24

* C2700 + Electroless nickel plated is used for the TJ series.

Construction



Component Parts

No.	Description	Material
1	Release button	Stainless steel 304
2	Guide 1	Stainless steel 304
3	Guide 2	Stainless steel 304
4	Chuck	Stainless steel 304
5	Seal	Special FKM (Fluoro coated)
6	Male connector body	C3604 (Electroless nickel plated)
7	Male elbow body	Stainless steel 316
8	O-ring	Special FKM (Fluoro coated)
9	Stud	C3604 (Electroless nickel plated)

KQB2 Series

Applicable Tubing: Metric Size, Connection Thread: M, R, Rc

Dimensions

Male Elbow: KQB2L



Applicable tubing O.D. (mm)	Connection thread R, M	Model	H (With across flange)	Note 1) ϕ D	L1	L2	A*	M	Note 2) Effective area (mm ²)	Weight (g)
ϕ 3.2	M5 x 0.8	KQB2L23-M5	8	8.3	13.1	14.8	16	12	2.6	6.5
	1/8	KQB2L23-01S	10		13.6	14.9	15.9		3	8
	1/4	KQB2L23-02S	14		13.7	15.2	16.8		3.5	7
ϕ 4	M5 x 0.8	KQB2L04-M5	8	9.1	13.7	15.2	16.8	12.6	3.5	7
	1/8	KQB2L04-01S	10		14.4	15.3	16.7		4.2	8.6
	1/4	KQB2L04-02S	14		14.7	16.3	19		3.5	9
ϕ 6	M5 x 0.8	KQB2L06-M5	8	11.4	14.7	16.3	19	13.6	11.4	10.2
	1/8	KQB2L06-01S	10		15.9	20.2	21.2		19.1	19.1
	1/4	KQB2L06-02S	14		21.6	22.2			31.2	31.2
ϕ 8	3/8	KQB2L06-03S	17	13.7	18.6	18.3	22	16.1	21.6	14.8
	1/4	KQB2L08-02S	14		19.1	21.5	23.6		20.8	20.8
	3/8	KQB2L08-03S	17		22.9	24.6			32.8	32.8
ϕ 10	1/8	KQB2L10-01S	12	16.6	20	19.7	24.9	17	21.6	20.4
	1/4	KQB2L10-02S	14		22.9	26.5			35.2	23.7
	3/8	KQB2L10-03S	17		24.3	27.5			34.5	34.5
ϕ 12	1/2	KQB2L10-04S	22	18.7	28.5	30.4		18.6	62.6	62.6
	1/4	KQB2L12-02S	14		22.6	24	28.6		27.4	27.4
	3/8	KQB2L12-03S	17		25.3	29.5			34.3	34.3
ϕ 16	1/2	KQB2L12-04S	22	24.6	29.5	32.4		20.8	60.8	60.8
	3/8	KQB2L16-03S	19		26.3	28	34.5		71	47
	1/2	KQB2L16-04S	22		27.3	31.8	37		100	62.6


* Reference dimensions after installation for R thread

Note 1) For the ϕ 16, this dimension refers to the O.D. of the release button.


Note 2) Value of FEP tubing.

Value of nylon tubing for ϕ 16 only.

(M5)



(R)



Male Branch Tee: KQB2T



Applicable tubing O.D. (mm)	Connection thread R, M	Model	H (With across flange)	Note 1) ϕ D	L1	L2	A*	M	Note 2) Effective area (mm ²)	Weight (g)
ϕ 3.2	M5 x 0.8	KQB2T23-M5	8	8.3	13.1	14.8	16	12	3.2	8.2
	1/8	KQB2T23-01S	10		13.6	14.9	15.9		3.4	9.6
	1/4	KQB2T23-02S	14		13.7	15.2	16.8		4.5	9.1
ϕ 4	M5 x 0.8	KQB2T04-M5	8	9.1	13.7	15.2	16.8	12.6	4.5	9.1
	1/8	KQB2T04-01S	10		14.4	15.3	16.7		6	10.6
	1/4	KQB2T04-02S	14		14.7	16.3	19		4.5	12.1
ϕ 6	M5 x 0.8	KQB2T06-M5	8	11.4	14.7	16.3	19	13.6	13.9	13.6
	1/8	KQB2T06-01S	10		15.9	20.2	21.2		22.5	22.5
	1/4	KQB2T06-02S	14		21.6	22.2			35	35
ϕ 8	3/8	KQB2T06-03S	17	13.7	18.6	18.3	22	16.1	26.3	20
	1/4	KQB2T08-02S	14		19.1	21.5	23.6		26.1	26.1
	3/8	KQB2T08-03S	17		22.9	24.6			38	38
ϕ 10	1/8	KQB2T10-01S	12	16.6	20	19.7	24.9	17	40.8	28.6
	1/4	KQB2T10-02S	14		22.9	26.5			31.5	31.5
	3/8	KQB2T10-03S	17		24.3	27.5			42.4	42.4
ϕ 12	1/2	KQB2T10-04S	22	18.7	28.5	30.4		18.6	70.4	70.4
	1/4	KQB2T12-02S	14		22.6	24	28.6		38.1	38.1
	3/8	KQB2T12-03S	17		25.3	29.5			39.7	39.7
ϕ 16	1/2	KQB2T12-04S	22	24.6	29.5	32.4		20.8	70.8	70.8
	3/8	KQB2T16-03S	19		26.3	28	34.5		71	64.4
	1/2	KQB2T16-04S	22		27.3	31.8	37		100	79


* Reference dimensions after installation for R thread

Note 1) For the ϕ 16, this dimension refers to the O.D. of the release button.

Note 2) Value of FEP tubing.

Value of nylon tubing for ϕ 16 only.

(M5)



(R)

